

# PARSUN

## OUTBOARDS



Parsun Outboards produce a line of high quality 2 stroke Outboards ranging from 2.5hp to 40hp in both long and short shaft, with manual and electric start models with tiller or remote control. The Parsun Outboard watch words are Quality, value for money, and customer satisfaction. Each major component part, such as cylinder head and gearbox is tested and re-tested at the factory before it is fitted to the engine. Once complete each Parsun marine engine is test-run for one hour to ensure quality and trouble free operation for our distributors, dealers, and most importantly for you, the retail end customers.

Quiet efficient 2 stroke marine engine  
 High grade marine aluminum alloy for ultimate corrosion protection  
 Tilt & trim with shallow water drive various positions  
 Twist grip throttle control for easy maneuverability & safety  
 Thermostat controlled water cooling system  
 Safety lanyard with emergency shutoff  
 Vibration reduction system for smooth performance

Adjustable steering friction for easier maneuverability  
 CDI ignition system for trouble free starting  
 Innovative large recoil wheel assists easy starting  
 Low emissions, quiet operation  
 Forward Control Available from 9.9 hp - 40hp  
 Heavy duty splined prop shaft  
 2 Year Warranty

HP - 2 Stroke	2.5	3.6	9.9	15	30	40
Overall Length mm (in.)	597 (23.5)	S 597 (23.5)	870 (33.4)	870 (33.4)	1106 (43.5)	1106 (43.5)
Overall Width mm (in.)	292 (11.3)	292 (11.5)	328 (12.9)	328 (12.9)	408 (16)	408 (16)
Overall Height mm (in.)	968 (38.1) 1095 (43.1)	968 (38.1) 1095 (43.1)	1039 (40.9) 1166 (45.9)	1039 (40.9) 1166 (45.9)	1213 (47.8) 1340 (52.8)	1213 (47.8) 1340 (52.8)
Transom Height mm (in.)	433 (17) 560 (22)	433 (17) 560 (22)	440 (17.3) 567 (22.3)	440 (17.3) 567 (22.3)	426 (16.8) 553 (21.8)	426 (16.8) 553 (21.8)
Weight kg	16.0 17.0	16.0 17.0	36.0 37.5	36.0 37.5	73.5 75.1	73.5 75.1
Full Throttle Range r/min	3800-5200	4200-5300	4500-5500	4500 - 5500	4500 - 5500	4500 - 5500
Maximum Output HP r/min	2.8 (1.8) @ 5000	3.6 (2.64) @ 5000	7.3 (9.9) @ 5000	11 (15) @ 5000	30 @ 5000	40 @ 5000
Idling Speed (Neutral) r/min	1250-1350	1250-1350	700 - 800	700 - 800	950 - 1050	950 - 1050
Engine Type	2-Stroke	2-Stroke	2-Stroke	2-Stroke	2 - Stroke	2 - Stroke
Cylinders	1	1	2	2	2	2
Displacement cm3	74.6	74.6	246	246	703	703
Bore x Stroke mm (in)	47 x 43	47 x 43	56 x 50	56 x 50	80 x 70	80 x 70
Ignition System	TCL	TCL	CDI	CDI	CDI	CDI
Control System	Tiller Control	Tiller Control	Tiller Control	Tiller Control	Tiller / Forward	Tiller / Forward
Starting System	Manual Start	Manual Start	Manual Start	Manual Start	Manual / Electric	Manual / Electric
Gear Positions	Forward - Neutral	Forward - Neutral	F-N-R	F-N-R	F-N-R	F-N-R
Gear Ratio	2.08 (27/13)	2.08 (27/13)	2.08 (27/13)	2.08 (27/13)	2 (26/13)	2 (26/13)
Trim and Tilt System	Manual Tilt	Manual Tilt	Manual Tilt	Manual Tilt	Manual Tilt	Manual Tilt
Fuel Tank Capacity	Integral 1.5	Integral 1.5	24	24	24	24
Maximum Fuel Usage L/h	1.4	1.8	5.1	7.9	15.1	20
Fuel / Oil Ratio	50lt / 1lt	50lt / 1lt	50lt / 1lt	50lt / 1lt	50lt / 1lt	50lt / 1lt
Gear Oil Capacity cm3	100	100	250	250	430	430
Propellor Options	3-71/4" X 6"	3-71/2" x 7"	3-91/2" x 11"	3-91/4" x 11"	3-111/8" x 13"	3-111/8" x 13"
Warranty	2 Year	2 Year	2 Year	2 Year	2 Year	2 Year



Unit 5 / 24 Mews Road, Fremantle, Western Australia , 6160  
 email: sales@westribs.com.au www.westribs.com.au

Tel: 08 9336 4418  
 Fax: 08 9336 4429